

Technical Data Sheet - Corrugated Carton 110911

Source document: C6_Scheda_110911.pdf

Parameter	Value
Code	110911
Article	395 x 295 x 250 H - American-style carton KBWFWK 36263 EB - UNBRANDED
Box type	American-style slotted carton
External dimensions	395 x 295 x 250 mm
Board composition	KBWFWK 36263 EB
Thickness	4.2 mm; tolerance 5%
Basis weight	663 g/m ² ; tolerance 8%
Carton weight	522 g; tolerance 8%
ECT	6.72 kN/m; tolerance 8%
BCT	294 kg; tolerance 8%
BCT with safety factor 3.7	80 kg; tolerance 8%
Burst strength	1653 kPa; tolerance 10%
Recycled fibre	60%
Virgin fibre	40%

Notes

- All material is subject to the general conditions specified in the GIFCO rules.
- The corrugated board manufactured by SIFA complies with the essential requirements of Regulation (EU) 2025/40 (PPWR).
- Raw materials: papers identified as BP, M, TB, W, F and T are made from 100% recycled fibres.
- Environmental identification under Italian Legislative Decree 152/2006, as amended: corrugated cardboard box/sheet
 - PAP 20 - paper collection. Where present: wooden pallet FOR 50; stretch film or shrink film LDPE 04; strapping PP 05. Check local collection rules.
- FSC-certified paper and food-grade paper are supplied if requested when placing the order.
- Optimum storage conditions: temperature +20 deg C and relative humidity 50-60%.

Issued 14 July 2026. The Italian original prevails.